



x4 POST
OPEN / CLOSED
FRONT LIFT
+ ACCESSORIES

TLS415AL0XR1
TLS415FD0XR1
TLS415ALCXR1
TLS415FDC0XR1
SERIES

TSLIFTS.COM



x4 POST OPEN/CLOSED FRONT

**AUTOMOTIVE + LIGHT TRUCK
GENERAL SERVICE**
15,000 LB. / 6.8T Capacity

x4 POST OPEN / CLOSED FRONT WHEEL ALIGNMENT OR SERVICE



x4 POST OPEN/CLOSED FRONT

WHEEL ALIGNMENT
OR SERVICE LIFTS

x4 Post Open / Closed Front Designs feature 'Camber Neutral' technology, double wall runways with "Z" rails, built in radius plate pockets & rear slip plates. Clear access, single point control with stainless steel cylinder air releases & engage 12 locking positions. Adjustable locking ladders 81"x 2-3/4" x 3/8" / 2057mm x 70mm x 9.5mm thick allow for accurate levelling. Power unit can be mounted on a front or rear column.

FEATURES

BUILT TO HIGHER QUALITY STANDARD/100% NORTH AMERICAN MADE :

Premium US Bucher 2HP / 1.5kw power unit.

CORROSION RESISTANT PROTECTION :

Steel components are wheel-a-brator shot blasted & acid washed before a "double bake" powder coat finish is applied.

SUPERIOR STRUCTURAL STRENGTH PROVIDES LONGER LIFE AND MORE PRECISE ALIGNMENTS :

Non flex double wall 23" / 584mm wide runways with built in "Z" rail. Heavy duty 10"x 8-3/8"x 1/4" wall / 254mm x 213mm x 6mm wall columns & 3" x 8-1/4" / 72mm x 210mm tube traverse beams.

GREATER FLEXIBILITY WITH MORE MODELS TO CHOOSE FROM :

Available in two runway lengths with built in wheel alignment or service deck. Lift can be ordered in red or blue.

PREMIUM OPTIONS + ACCESSORIES CAN EXPAND THE CAPABILITIES + SERVICE LIFE

Stainless steel radius plates & rear steer plates, built in tire inflation hoses, removable work steps, LED runway lighting & premium long life 5 yr warranty HD jacking beams.

LOWER MAINTENANCE COSTS :

Zirk style grease fittings at all 1-1/2" / 38mm plated hinge pins. Runway under rear slip plates is open to prevent water & dirt collecting. Thirty 7/8" / 22mm

enclosed plated steel slip plate balls provide better support with minimal maintenance.

EXTENDED LIFE "NON TWIST" CABLE DESIGN :

Machined steel nickel plated 9" / 229mm pulleys with bronze self lubricating bushings. Non spin fatigue resistant 9/16" / 14mm cables are routed on double stacked pulleys (versus four stacked) to reduce stress & wear.

LOW PRESSURE HYDRAULICS PROVIDES LONGER LIFE

4" ID x 65" / 102mm ID x 1651mm cylinder is mounted under the runway and use a premium "Parker" seal & wear ring with chrome plated plunger shaft.





Technical drawing of the 120 PSI Air Tower, showing front and side views with dimensions.

Front View Dimensions:

- Overall height: $137\frac{1}{2}"$
- Distance from top to first motor: $119"$
- Distance between motors: $41"$
- Distance from second motor to bottom: $60\frac{1}{2}"$
- Overall width: $143"$
- Distance from left side to first motor: $40\frac{1}{8}"$
- Distance between motor bases: $247\frac{1}{2}"$
- Distance from first motor base to second motor base: $160\frac{1}{8}"$
- Distance from second motor base to right side: $231\frac{1}{4}"$
- Distance from first motor base to right side: $76"$
- Distance from second motor base to right side: $84\frac{1}{8}"$

Side View Dimensions:

- Overall height: $86"$
- Overall width: $225\frac{1}{4}"$
- Distance from left side to motor base: $8\frac{3}{8}"$
- Distance from motor base to right side: $7\frac{3}{8}"$
- Distance from motor base to right side: $10\frac{1}{2}"$

Other Information:

- VERTICAL TRAVEL: $66\frac{3}{4}"$
- MOTOR: 230V 1 PH 2HP
- AIR: 120 PSI

MOTOR: 230V 1PH 2HP
AIR: 120 PSI

OPEN / CLOSED FRONT ADDITIONAL FEATURES + ACCESSORIES

Increase productivity & versatility

ADDITIONAL FEATURES

+ 'CAMBER NEUTRAL' ADJUSTABLE FRONT ARMS




TLS-RJ75



TLSTP

**+ PULLEY/CABLES/ DOUBLE
WALL DECK W Z RAIL**



TLSMWS



100% DESIGNED
+ BUILT IN
NORTH AMERICA



tllifts.com





TOTAL AUTOMOTIVE
LIFTING SOLUTIONS INC.

2300 Speers Rd Oakville, On L6L 2X8

t. (877) 799-5438

fax. (905) 891-1214

tllifts.com
