



4 POST

TLS430FDCRx1 / TLS435FDCRx1

MEDIUM AND LIGHT DUTY GENERAL SERVICE LIFTS

100% DESIGNED AND BUILT IN NORTH AMERICA

4 POST

30,000 LB. / 13.6T OR 35,000 LB. / 15.9T CAPACITY

MEDIUM DUTY COMMERCIAL LIFTS CAPABLE OF SAFELY SERVICING VEHICLES SMALL AND LARGE




STANDARD FEATURES



▲ North American Power Unit / Air Mechanical Locking System with Regulator



▲ 13" / 330 mm Machined Pulleys with 5/8" / 15.9mm Cables



▲ 24" / 610mm Double Wall Non Sag Runways

OPTIONAL FEATURES



▲ Rolling Air Hydraulic Jacks #TLS-RJ15

4 POST ALIGNMENT

4 POST SERVICE 30,000 LB. / 13.6T
OR 35,000 LB. / 15.9T CAPACITY

STANDARD TLS430FDCRx1 / TLS435FDCRx1
EXTENDED TLS430FDCXx1 / TLS435FDCXx1
EXTRA LONG TLS430FDCEx1 / TLS435FDCEx1


AT TLS OUR GOAL IS TO BUILD LIFTS THAT LAST LONGER, PERFORM BETTER AND COST LESS TO OPERATE

SPECIFICATIONS	STD	EXT	X-LONG
Capacity	30,000 lb. / 13.6T or 35,000 lb. / 15.9T		
Overall Length	328-1/4" / 8338mm	364-1/4" / 9252mm	400-1/4" / 10166mm
Deck Length	261" / 6629mm	297" / 7544mm	333" / 8458mm
Overall Width	153" / 3886mm		
Deck Width	24" / 610mm		
Lower Height	10" / 254mm		
Raised Height	70-1/4" / 1784mm		
Maximum Wheelbase	256" / 6502mm	292" / 7417mm	328" / 8331mm
Lift Time	100 seconds		
Power Requirements	230 Volts AC - 60 Hz - 1 Ph - 20 Amp		
Shipping Weight	7,500 lbs. / 3.4T		
Standard Model	TLS430FDCRx1 / TLS435FDCRx1		
Extended Model	TLS430FDCXx1 / TLS435FDCXx1		
Extra Long Model	TLS430FDCEx1 / TLS435FDCEx1		

FEATURES

- Built to higher quality standard; 100% North American made** - premium US Monarch (Bucher) 4HP / 3kw power unit.
- Corrosion resistant protection** - steel components are wheel-abrator shot blasted and acid washed before a "double bake" powder coat finish is applied.
- Superior structural strength provides longer life** - Non flex double wall 24" / 610mm wide runways with built in "Z" rail. Heavy duty 10" x 8-3/8" / 254mm x 213 mm wall columns and 4" x 8" / 102mm x 204mm tall tube traverse beams.
- Greater flexibility with more models to chose from** - Chose between a 30,000lb. / 13.6T or 35,000lb. / 15.9T version. Available in three (3) runway lengths with service deck or optional with radius plate pockets. Lift can be ordered in red or blue.
- Premium options and accessories can expand the capabilities and service life** - rear steer plates, built in tire inflation hoses, removable work steps, LED runway lighting and premium 15,000lb. / 6.8T jacking beams
- Lower maintenance costs** - Zirk style grease fittings at all 1 1/2" / 38mm plated hinge pins. Runway under rear slip plates is open to prevent water and dirt collecting. Thirty 7/8" / 22mm enclosed plated steel slip plate balls provide better support with minimal maintenance.
- Extended Life "Non Twist" Cable design** - Machined steel nickel plated 12-3/4" / 324mm pulleys with bronze self lubricating bushings. Non spin fatigue resistant 5/8" / 16mm cables are routed on double stacked pulleys (versus four stacked) to reduce stress and wear.
- Low pressure hydraulics provides longer life** - 5" ID x 69" / 127 x 1753 cylinder is mounted under the runway and use a premium "Parker" seal and wear ring with chrome plated plunger shaft.
- Designed for optimum productivity** - Single point control with stainless steel cylinder air releases engage 12 locking positions. Adjustable locking ladders 87" x 3 3/4" x 3/8" / 2210mm x 95mm x 9.5mm thick allow for accurate levelling. Power unit can be mounted on a front or rear column. Built in runway compressed air outlets front and rear. Lifts 71" / 1803mm from the floor.

EQUIPMENT FOOTPRINT



CONTACT US NOW

WWW.TLSLIFTS.COM OR CALL (877) 799-5438

